



SERVICE CONNECTION FITTINGS SCHEDULE - OPTION 1 CERAMIC JUNCTION			
FITTING	DIA (mm)	DESCRIPTION	QTY.
①	150 x 100	CLARK'S POTTERIES CERAMIC PLAIN ENDED 45 WYE JUNCTION, OUTSIDE DIAMETER 192mm	1
②	SC215	FLEX-SEAL OR DUX FERNCO (OR SIMILAR APPROVED) STANDARD COUPLING, TYPE "A" OR "B" EPDM RUBBER, GRADE 316 STAINLESS STEEL LOCKING AND SHEAR BANDS	2
③	AC5144	FLEX-SEAL OR DUX FERNCO (OR SIMILAR APPROVED) ADAPTOR COUPLING, TYPE "A" OR "B" EPDM RUBBER, GRADE 316 STAINLESS STEEL LOCKING BANDS	1
④	110 O.D.	uPVC SN16 PLAIN ENDED PIPE TO AS/NZS 1260, 300mm LONG (NO RAMP RISER) OR LENGTH TO SUIT (WHERE A RAMP RISER IS REQUIRED)	1
⑤	110 I.D.	SN16 SEWER GRADE SCREW CAP FITTING (INCLUDING SCREW CAP) THREADED ON OUTER FACE FOR SCREW CAP, FITTING ENDS 110mm ID SUITABLE FOR JOINTING WITH SOLVENT CEMENT ONTO 110 OD uPVC PIPE. ONLY 2 PIECE FITTINGS (i.e. INCLUDING CAP) ARE APPROVED.	1
SERVICE CONNECTION FITTINGS SCHEDULE - OPTION 2 PVC 45 WYE JUNCTION			
FITTING	DIA (mm)	DESCRIPTION	QTY.
①	160 O.D. x 110 I.D.	TYPE "A" uPVC 45 WYE JUNCTION, WITH SOCKETTED BRANCH	1
②	AC2154	FLEX-SEAL OR DUX FERNCO ADAPTOR COUPLING, TYPE "A" OR "B" EPDM RUBBER, WITH GRADE 316 STAINLESS STEEL LOCKING BANDS	2
③	-	NOT REQUIRED	-
④	110 O.D.	SN16 SEWER GRADE PLAIN ENDED PIPE TO AS/NZS 1260, 300mm LONG (NO RAMP RISER) OR LENGTH TO SUIT (WHERE RAMP RISER IS REQUIRED)	1
⑤	110 I.D.	SN16 SEWER GRADE SCREW CAP FITTING (INCLUDING SCREW CAP) THREADED ON OUTER FACE FOR SCREW CAP, FITTING ENDS 110mm ID SUITABLE FOR JOINTING WITH SOLVENT CEMENT ONTO 110 OD uPVC PIPE. ONLY 2 PIECE FITTINGS (i.e. INCLUDING CAP) ARE APPROVED	1

Rodney
DISTRICT COUNCIL

Head Office: 50 Centreway Road, Orewa
Private Bag 500, Orewa, 1461, New Zealand
Tel: 0800 4265169, Fax (09) 4267280
Email: info@rodney.govt.nz

STANDARD DETAIL:

**WASTEWATER SERVICE
CONNECTION DETAILS
150MM NOMINAL DIA
CONCRETE PUBLIC DRAIN**

Copyright on this Drawing is Reserved
DATE: June 2005
NOT TO SCALE

RDC NO: SHEET NO: REV:

18000 5.8